

The HE500 series appliances are designed for edge computing, small remote sites, and for disaster recovery. More information at www.scalecomputing.com - 877.722.5359

HE500	HE550	HE550F	HE500T	HE550TF
CPU: Intel® Xeon® E-2100 <ul style="list-style-type: none"> 1 x E-2124 4C/4T 3.3GHz 1 x E-2134 4C/8T 3.5GHz 1 x E-2136 6C/12T 3.3 GHz RAM: <ul style="list-style-type: none"> Size: 32GB, 64GB Type: DDR4 Storage: <ul style="list-style-type: none"> 4 x HDD 1TB, 2TB, 4TB, 8TB Network Access: <ul style="list-style-type: none"> 4 x 1GbE 4 x 10GbE SFP+ Dimensions: 1U Rack Height <ul style="list-style-type: none"> 1.7" (43mm) H x 17.1" (434mm) W x 19.6" (498mm) D Power: <ul style="list-style-type: none"> 2 x 450W Power Supply Units Certifications: <ul style="list-style-type: none"> UL/CB, CE, FCC 	CPU: Intel® Xeon® E-2100 <ul style="list-style-type: none"> 1 x E-2124 4C/4T 3.3GHz 1 x E-2134 4C/8T 3.5GHz 1 x E-2136 6C/12T 3.3 GHz RAM: <ul style="list-style-type: none"> Size: 32GB, 64GB Type: DDR4 Storage: <ul style="list-style-type: none"> 1 x SSD 480GB, 960GB 3 x HDD 1TB, 2TB, 4TB Network Access: <ul style="list-style-type: none"> 4 x 1GbE 4 x 10GbE SFP+ Dimensions: 1U Rack Height <ul style="list-style-type: none"> 1.7" (43mm) H x 17.1" (434mm) W x 19.6" (498mm) D Power: <ul style="list-style-type: none"> 2 x 450W Power Supply Units Certifications: <ul style="list-style-type: none"> UL/CB, CE, FCC 	CPU: Intel® Xeon® E-2100 <ul style="list-style-type: none"> 1 x E-2124 4C/4T 3.3GHz 1 x E-2134 4C/8T 3.5GHz 1 x E-2136 6C/12T 3.3 GHz RAM: <ul style="list-style-type: none"> Size: 32GB, 64GB Type: DDR4 Storage: <ul style="list-style-type: none"> 4 x SSD 240GB, 480GB, 960GB Network Access: <ul style="list-style-type: none"> 4 x 1GbE 4 x 10GbE SFP+ Dimensions: 1U Rack Height <ul style="list-style-type: none"> 1.7" (43mm) H x 17.1" (434mm) W x 19.6" (498mm) D Power: <ul style="list-style-type: none"> 2 x 450W Power Supply Units Certifications: <ul style="list-style-type: none"> UL/CB, CE, FCC 	CPU: Intel® Xeon® E-2100 <ul style="list-style-type: none"> 1 x E-2124 4C/4T 3.3GHz 1 x E-2134 4C/8T 3.5GHz 1 x E-2136 6C/12T 3.3 GHz RAM: <ul style="list-style-type: none"> Size: 32GB, 64GB Type: DDR4 Storage: <ul style="list-style-type: none"> 4 x HDD 1TB, 2TB, 4TB, 8TB 8 x HDD 4TB, 8TB Network Access: <ul style="list-style-type: none"> 2 x 1GbE* Dimensions: <ul style="list-style-type: none"> 17" (430mm) H x 6.9" (175mm) W x 22.3" (565.7mm) D Power: <ul style="list-style-type: none"> 2 x 550W Power Supply Units Certifications: <ul style="list-style-type: none"> UL/CB, CE, FCC <small>* Single node configuration only</small>	CPU: Intel® Xeon® E-2100 <ul style="list-style-type: none"> 1 x E-2124 4C/4T 3.3GHz 1 x E-2134 4C/8T 3.5GHz 1 x E-2136 6C/12T 3.3 GHz RAM: <ul style="list-style-type: none"> Size: 32GB, 64GB Type: DDR4 Storage: <ul style="list-style-type: none"> 4 x SSD 240GB, 480GB, 960GB Network Access: <ul style="list-style-type: none"> 2 x 1GbE* Dimensions: <ul style="list-style-type: none"> 17" (430mm) H x 6.9" (175mm) W x 22.3" (565.7mm) D Power: <ul style="list-style-type: none"> 2 x 550W Power Supply Units Certifications: <ul style="list-style-type: none"> UL/CB, CE, FCC <small>* Single node configuration only</small>
1U - Rack	1U - Rack	1U - Rack	Tower	Tower
Rack Models Include: Rack Rails, Power Cables, Bezel, and Quick Start Guide			Tower Models Include: Power Cables, Security Door, and Quick Start Guide	

HyperCore OS v8			
Guest OS Support	Windows:	Linux:	Other:
	Windows Server 2019, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012, Windows Server 2008, Windows Server 2008 R2, Windows Server 2003 R2, Windows 10, Windows 8 (64 bit), Windows 7, Windows Vista	RHEL/CentOS SUSE Linux Enterprise <i>See Hypercore Support Matrix for details.</i>	Other operating systems that run on virtualized x86 and x64 platforms may work, but they will not be fully supported by Scale Computing.
Scalability	Customer can add up to 8 nodes per cluster with no disruption to operation. Contact Scale Computing for information on designing clusters larger than 8 nodes.		
Management	<ul style="list-style-type: none"> Web browser-based GUI, email, and Syslog notifications Automatic VM failover and live migration between nodes Built in hypervisor (included) 		